P10 Pro Datasheet

Product Overview

The P10 Pro is a high flow servo proportional valve engineered for demanding heavy duty applications. With strong dynamic stability and robust construction, it manages large volumes of hydraulic power with confidence, supporting presses, power and energy systems, and large-scale industrial automation. It is designed for environments where consistent control under higher loads is essential.

Key Features

- Integrated electronics with spool position feedback
- Rated flow of 160 l/min (at 70 Bar ΔP)
- Drop-in replacement on NG10 port pattern
- Bandwidth > 65 Hz
- Various power-off positions
- Chip shear capability of > 700 N
- Mass of 4 kg

Customisation

The P10 Pro is designed to be easily configurable. The standard options are set out in the SKU selection on page 6. Non-standard customisations are also available, and our sales team would be happy to discuss your requirements.

Contents

Technical Data.....2
Performance Graphs.....3
Standards References.....4
Unit Dimensions.....4
Mounting Dimensions.....5
LED Status.....5
SKU Selection.....6

Contact Us

If you have any questions about using the P10 Pro, or if you need a non-standard configuration, we would be happy to hear from you.

Contact us using the details below and one of our team will be there to assist you.

33 Colston Avenue, Bristol, BS1 4UA
+44 (0)333 090 5140
sales@domin.com
domin.com



DOMIN

Technical Data

General Data

Design		Direct Drive Servo Proportional Valve
Actuation		Rotary-Linear
Size		NG10
Mounting Interface		ISO 4401-05-04
Ambient Temperature	°C (°F)	–20 to +60 (–4 to +140)
Mass	kg (lb)	4 (8.8)
Vibration Resistance[1]	g	30
Shock Resistance[2]	g	50

Hydraulic Data

Max. Operating Pressure (P, A, B)	Bar (psi)	350 (5,000)
Max. Operating Pressure (T)	Bar (psi)	250 (3,600)
Fluid		Hydraulic Oil DIN 51524
Fluid Temperature	°C (°F)	–20 to +80 (–5 to +175)
Filtration		ISO 4406 (1999) 18/16/13
Viscosity	cSt	5 to 500
Rated Flow[3]	l/min (gpm)	40 to 160 (10.6 to 42)
Flow Maximum	l/min (gpm)	250 (66)
Pressure Gain	%/%	> 40
Leakage at 100 bar	l/min (gpm)	< 1 (0.4)


Static/Dynamic Data

Response Time at 100%[4]	ms	< 20
Frequency Response (-3dB gain, ±25% signal)[4]	Hz	> 65
Frequency Response (-90deg phase, ±25% signal)[4]	Hz	> 65
Hysteresis	%	< 0.2
Threshold	%	< 0.1
Null Shift	%	< 1


1. BS EN 60068-2 (20-35 Hz, 16 g for 15 minutes per axis, 35-2000 Hz, 35 g for 15 minutes per axis).
2. BS EN 60068-2 (20 shocks 50 g in Z axis).
3. Rated at a ΔP of 70 bar (35 bar per edge), 160 l/min only available for Axis cut valves.
4. Measured as 90% output rise time with Δ70 bar P-T (two control edges).

Performance Graphs

Step Response[1]



Frequency Response[1]





1. Measured at a 70 bar pressure drop.

Standards References

EMC Regulations:	Immunity: EN 61000-6-2, Emission: EN 61000-6-3
Performance Tests:	ISO 10770-1
Pressure Rating:	ISO 10771
Hydraulic Interface:	ISO 4401-05-04

Unit Dimensions






Nominal dimensions are displayed in mm, [] indicates inches. Not to scale.

Mounting Dimensions

		P	A	B	T	T	X1[1]	Y1	F1	F2	F3	F4
Diameter	mm	11.2	11.2	11.2	11.2	11.2	6.3	6.3	M6	M6	M6	M6
X Position	mm	27	16.7	37.3	3.2	50.8	-8.0	62.0	0	54	54	0
Y Position	mm	6.3	21.4	21.4	32.5	32.5	11	11	0	0	46	46



Bolts (F1, F2, F3, F4)

Type: M6 x 120 DIN EN ISO 4762-10.9

Required Torque: 13 Nm

O-Rings (P, A, B, T, T1, X(1) , Y (1))

Type: 5x ISO 3601-1-014

Type(1): 2x ISO 3601-1-011

1. .Valve includes seal grooves for X and Y ports for installation in existing systems – X and Y connections are NOT required for valve operation. Port X & Y not in use, seals are for blanking only.operation. Port X & Y not in use, seals are for blanking only.

LED Status

LED Colour	LED State	Motor Drive State	Valve State
Green	Solid - On	Motor Drive On	Valve OK
	Flashing	Motor Drive On	Warning Present
Red	Solid - On	Motor Drive Off	Valve OK
	Flashing	Motor Drive Off	Error Present

SKU Selection

Use our SKU builder to configure your Domin Valve. If you need a non-standard setup or a bespoke option, just get in touch – we can tailor a solution to suit your exact requirements.

P10 Pro - 1 - 2 - 3 - 4 - 5 - 6 - 7 - 8 - Custom ID

Code 1	Rated Flow
40 to 160	l/min
40 to 160R	l/min, Reverse

Code 2	Flow Behaviour
A	Axis
B	Float Centre
D	Blocked
O	Overlap
X	Special Enquiries

Code 3	I/O
A	± 10 V
B	± 20 mA
C	4 to 20 mA
D	± 5 V
E	± 5 mA
F	± 10 mA
X	Special Enquiries

Code 4	Power-Off Position
B	Float
C	Passive
D	Blocked
PA	A Bias
PB	B Bias
X	Special Enquiries

Code 5	Electrical Connector
E	6 pin + PE
E4	4 pin
X	Special Enquiries

Code 6	Enable Mode
N	No Enable Functionality
Y	Enable Mode

Code 7	Fluid Type
R	Recommended Oil
X	Special Enquiries

Code 8	Seal Material
N	Nitrile
V	Viton
X	Special Enquiries

Code 9

Code 1 Rated Flow

Any value in range 40 to 160 LPM rated at 35 bar ΔP per control edge. R – Suffix for reversal of A and B port e.g. 160R

$$Q = Q_N \sqrt{\frac{P}{70}}$$

Q = Calculated flow
Q_N = Rated flow (at 70 bar)
P = Pressure





Code 2 Flow Behaviour

The flow behaviour of the valve is defined in two sections, the mechanical spool cut that makes the hydraulic connections and the software characteristic (flow map) that controls the flow with respect to input demand.

By default, each hydraulic connection will have a default flow mapping, and the code will be simplified to a single letter. If a non-default flow mapping is desired a second letter will denote the flow map.
E.g., an Axis-Linear valve will have a single code A, an Axis-Deadband valve will have the code AD.

Please enquire for other options.


Hydrualic Connections

Code	Hydrualic Connection	Description	Symbol	Deafult Flow Map
A	Axis	1% overlap		Linear
B	Float	5% overlap P 5% underlap T		Deadband
D	Blocked	5% overlap		Deadband
O	Overlap	3% overlap		Gradual
X	For other options please enquire			


Flow Map

Code	Flow Map	Description
A	Linear	100% flow gain across full range
D	Deadband	0% flow gain between ±10% flow demand
O	Gradual	0% flow gain between ±10% flow demand


A - Linear



D - Deadband



O - Gradual



Code 3 Control Methods

Code	Input Signal	Input Impedance	Output Signal	Output Load Impedance
A	± 10 V	200 kΩ	± 10.5 V	-
D	± 5 V		± 5.25 V	
E	± 5 mA	402 Ω	± 5.25 mA	600 Ω
F	± 10 mA		± 10.5 mA	
B	± 20 mA		± 21 mA	
C[1]	4 to 20 mA		3.8 to 21 mA	600 Ω
X	For other options please enquire			

1. For 4 to 20 mA input signal, a current input below 2 mA will disable the motor drive
2. Valves with a current command signal use a 0.1% tolerance shunt resistor to measure demand current.
3. For differing input and output signals, use two letters, e.g. AC denotes ± 10 V Input and 4 to 20 mA output

Electrical



Supply Voltage (Operational)	V	22 to 30
Supply Voltage (Absolute)[1]	V	-0.5 to 33
Current Consumption[2]	A	0.8
Peak Current Draw[3]	A	8

1. Conditions outside the absolute maximum ratings may cause permanent damage to the valve. These are absolute ratings only. Operation of the product outside of the nominal operating conditions is not guaranteed and may affect product reliability
2. Approximate current consumption for 100 Hz at 25 % amplitude
3. The valve supply must be protected with a 10 AT fuse or equivalent overcurrent protection device

Code 4 Power-Off Position

Power-off position defines the hydraulic connection that the valve will move to when the power / input is removed, or if the valve errors, or if the enable pin (if enable mode Y) is low.


Vibration resistance for power-off position is rated to BS EN 60068-2-6 (20-57 Hz, 1.5 mm peak, 58-2000 Hz, 10 g per axis).

Code	Name	Description	Symbol
B	Float	P blocked, A, B, T connected	
C	Passive	Spool is intended to return to centre passively under typical flow conditions	
D	Blocked	All ports blocked	
PA	A Bias	P connected to A, B connected to T	
PB	B Bias	P connected to B, A connected to T	
X	For other options please enquire		

Code 5 Electrical Connectors

6 + PE Circular Connector (E)

Type:	Case-Mounted
Termination:	Connector according to EN 175201-804/MIL 5015 equivalent, shell size 14
Number of Contacts:	7




Pin	Function	Description
A	Supply +	+24 V
B	Supply 0 V	0 V
C[1]	Output – Enable input	Output 0 V Reference Drive enable input
D	Input +	Differential input signal, +
E	Input –	Differential input signal, –
F	Output +	Output Signal
G	Earth	-

1. When the enable function is selected, the function of pin C is the enable input. This replaces the standard pin function.

4 Pin Circular Connector (E4)

Type:	Case-Mounted
Termination:	Connector according to EN 175201-804/MIL 5015 equivalent, shell size 14
Number of Contacts:	4



Pin	Function	Description
A	Supply +	+24 V
B	Input +	Differential input signal, +
C	Input –	Differential input signal, –
D	Supply 0 V	0 V

Code 6 Enable Modes

Valves can be provided with an enable function. This allows the valve to be enabled or disabled by varying the voltage into the enable pin. Note that valves with a code C command type can also be enabled or disabled using the command signal; see the corresponding table above for further details. Enable function is only applicable with Code E electrical connector option.

N	No Enable Functionality
Y	Enable mode

Normal Operating Conditions		Units	Min.	Typical	Max.
Enable Mode	Drive On	V	9	-	30
	Drive Off	V	0	-	5
	Input Impedance	kΩ	-	15	-

Code 7 Fluid Types

R	Recommended - any hydraulic oil in accordance with DIN 51524, filtered in accordance with ISO4406 18/16/13. Compatibility with water-free synthetic fluids available on enquiry.
X	For other options please enquire

Code 8 Seal Materials

N	Nitrile (Shore 90)
V	Viton (Shore 85)
X	For other options please enquire